09310140/31717=

Preparation of strained Si/SiGe on insulator by hydrogen induced layer transfer technique

Patent number:

TW512487

Publication date:

2002-12-01

HUANG LIJUAN (CN); CANAPERI DONALD F (US);

CHU JACK O (US); OTT JOHN A (US); D EMIC

CHRISTOPHER P (US)

Applicant:

IBM (US)

Classification:

- international:

H01L21/762

- european:

Application number: TW20010123782 20010926 Priority number(s): US20000675840 20000929

WO0227783 (A US6524935 (B1

Abstract of TW512487

A method for forming strained Si or SiGe on relaxed SiGe on insulator (SGOI) is described incorporating growing epitaxial Si1-yGey layers on a semiconductor substrate, implanting hydrogen into a selected Si1 yGe1-y layer to form a hydrogen-rich defective layer, smoothing surfaces by Chemo-Mechanical Polishing, bonding two substrates together via thermal treatments and separating two substrates at the hydrogen-rich defective layer. The separated substrates may have its upper surface smoothed by CMP for epitaxial deposition of relaxed Si1-yGey, and strained Si1-yGey depending upon composition, straine Si, strained SiC, strained Ge, strained GeC, and strained Si1-yGeyC.

Data supplied from the esp@cenet database - Worldwide

2004/10/27

http://v3.espacenet.com/textdoc?DB=EPODOC&IDX=TW512487&F=0